

160 Oil Resistant Unlined



Unsupported PVC coating

DESCRIPTION

- Fully coated
- Scalloped edge
- Raised finish
- Special hydrocarbon treatment
- Non-powdered, "slip-on" treatment
- Anatomical shape



BENEFITS

- A thin, light glove with a "second skin" feel
- Seals and protects the hand against chemicals while remaining flexible
- Impermeable for working in damp or greasy environments
- Surface enables a secure grip on slippery objects
- Easy to put on and remove, lint-free, dust-free
- Designed for easy movement and continuous wear
- Extended protection on the forearm

RECOMMENDED FOR THESE RISKS:

Chemicals

Oils

Hydrocarbons

RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Alkaline components

Chemical industry / Solvents

Petrochemistry

AVAILABLE SIZES

8/M • 9/L • 10/XL

LENGTH

Dependent on size, in mm (flat)

300-310

PACKAGING

Pairs per pack/box

10/240

COLOUR OF SUPPORT/COATING

Blue

THICKNESS

in mm

0,30

RECOMMENDATIONS FOR USE

- Do not use with chemicals other than those tested without prior trials
- The stated impermeability performance level (EN374-3) does not reflect the actual protection level at the place of work
- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary

Cat. III	EN388 - 1994	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	EN 374-2 - 1994	EN 374-3 - 1994	HYDROCHLORIC ACID 36% 0 1 2 3 4 5 6	KEROSENE 0 1 2 3 4 5 6
		TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4			CAUSTIC SODA 40% 0 1 2 3 4 5 6	
0123	3000						

EC compliance certificate delivered by the notified body 0120

[Updated 13/10/11]

SHOWA BEST GLOVE

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

SHOWA

The Ultimate in Comfort and Dexterity